

Scanned by CamScanner

NRA Series | Brushless motor

Du-Pas®

- Cordless Transducerized Tools -




| Model No. | Voltage | Drive Size | Screw Size | Torque Range | | Free Speed | Noise Level dB(A) | Weight w/o battery | |
|-----------|---------|------------|------------|--------------|----------|---------------|-------------------------|--------------------|------|
| | V | inch | mm | N.m in-lb | | rpm | | kg | lb |
| NRA-10H2 | 20 | 1/4" Hex. | M4 ~ M5 2 | | 18 - 89 | 400 - 950 | <75 | 1.55 | 3.42 |
| NRA-10S2 | | 1/4" Sq. | | 2 - 10 | | | | | |
| NRA-10S3 | | 3/8" Sq. | | | | | | | |
| NRA-16H2 | 20 | 1/4" Hex. | M5 ~ M6 | 4 - 16 | 36 - 142 | 300 - 550 | <75 | 1.55 | 3.42 |
| NRA-16S2 | | 1/4" Sq. | | | | | | | |
| NRA-16S3 | | 3/8" Sq. | | | | | | | |
| NRA-30S3 | 20 | 3/8" Sq. | M6 ~ M8 | 8 - 30 | 71 - 266 | 200 - 350 | <75 | 1.55 | 3.42 |

Spanner and marking color ring are included with the tool.

NPA Series | Brushless motor

- Cordless Transducerized Tools -

Du-Pas®



SPECIFICATIONS

| Model No. | Voltage | Drive Size | Screw Size | Torque Range | | Free Speed | Noise Level | Weight w/o battery | |
|-----------|---------|------------|------------|--------------|----------|---------------|----------------|--------------------|------|
| | v | inch | mm | N.m | in-lb | rpm | dB(A) | kg | lb |
| NPA-03H2 | 20 | 1/4" Hex. | M3 ~ M4 | 0.8 - 3 | 7 - 26 | 230 - 1500 | <75 | 1.39 | 3.08 |
| NPA-03S2 | | 1/4" Sq. | | | | | | | |
| NPA-03S3 | | 3/8" Sq. | | | | | | | |
| NPA-08H2 | 20 | 1/4" Hex. | M3 ~ M5 | 2 - 8 | 18 - 71 | 180 - 1200 | <75 | 1.39 | 3.08 |
| NPA-08S2 | | 1/4" Sq. | | | | | | | |
| NPA-08S3 | | 3/8" Sq. | | | | | | | |
| NPA-12H2 | 20 | 1/4" Hex. | M4 ~ M6 | 3 - 12 | 26 - 106 | 120 - 800 | <75 | 1.39 | 3.08 |
| NPA-12S2 | | 1/4" Sq. | | | | | | | |
| NPA-12S3 | | 3/8" Sq. | | | | | | | |
| NPA-18H2 | 20 | 1/4" Hex. | NAT OF NAC | 4 10 | 35 - 159 | 80 - 500 | <75 | 1.39 | 3.08 |
| NPA-1853 | | 3/8" Sq. | M5 ~ M6 | 4 - 18 | | | | | |


18V **Cordless Shut-off Impact Wrench/Screwdriver**



IWT series Brushless Motor

3 - 120 N.m.

LED Indicators: REVERSE OK NOK



Advanced brushless motor provides longer motor life and greater efficiency.



LED light for work area illumination.

1. Non-contact switch provides longer life with less downtime. 2. Variable speed control trigger.

Li-ion battery offers longer life with no memory effect.

Mini USB port for downloading data from the motor.

F/R button for ease of ergonomic operation.

Shock absorbing, ergonomic grip provides less fatigue with well-balanced operation.

> Smart battery with capacity indicator.

Unique Patented Shut Off System

Torque control function: 50 programmable stage settings.



LOW BATTERY WARNING

CHANGE BATTERY

Torque stage & error display

Torque setting button

SPECIFICATIONS

18V DAb Li-ion

| Model No. | Volt | Drive Size inch | Screw Size | Torque Range | | Max. Torque | | Free Speed | Weight w/o Battery | | Noise Level |
|-----------|------|-----------------------|---------------|--------------|-------------|-------------|-------|---------------|--------------------|------|----------------|
| | V | | mm | N.m | ft-lb | N.m | ft-lb | rpm | kg | lb | dB(A) |
| IWT-025H2 | 18 | 1/4" Hex. | M5,M6 | 3 - 25 | 2.2 - 18.4 | 40 | 29.5 | 2400 | 1.0 | 2.2 | 71 |
| IWT-032H2 | 18 | 1/4" Hex. | M6 | 6 - 32 | 4.4 - 23.6 | 90 | 66.4 | 2400 | 1.0 | 2.2 | 71 |
| IWT-032S3 | 18 | 3/8" Sq. | | | | | | | | | |
| IWT-055S3 | 18 | 3/8" Sq. | M8 | 15 - 55 | 11.1 - 40.6 | 120 | 88.5 | 2400 | 1.1 | 2.43 | 71 |
| IWT-055S4 | 18 | 1/2" Sq. | | | | | | | | | |
| IWT-100S4 | 18 | 1/2" Sq. | M8,M10 | 25 - 100 | 18.4 - 73.8 | 180 | 132.8 | 2400 | 1.1 | 2.43 | 71 |
| IWT-120S4 | 18 | 1/2" Sq. | M10,M12 | 30 - 120 | 22.1 - 88.5 | 210 | 154.9 | 2400 | 1.3 | 2.87 | 71 |

The specification data is based on prototype testing in a controlled environment. Full production model specification data will be verified prior to market release.