





Features



Support Hanger Support Hanger is available on each model



Gauge Indicator for recognition on tension adjustment



Drum Lock System Drum lock for cable replacement



KLSB Series

Advantages

- Reduces operator fatigue
- Increases safety when working with heavy load
- Steel core wire rope for longer life

Applications

- Body shops
- Assembly lines



KSB Series

Advantages

- Reduces operator fatigue
- No need of electric or pneumatic power
- Increases safety when working with heavy load
- Steel core wire rope for longer life
- Provision of thrust bearing on top hook for smooth operation

Applications

- Body shops
- Assembly lines



KHRB Series

Advantages

- Reduces operator fatigue
- Increases safety when working with heavy load
- Effective use of space
- Provision of thrust bearing on top hook for smooth operation
- High quality air hose made of polyurethane



KLSB Series

Model No	Wire Rope DIA (mm)	Capacity (Kgs)	Travel (Mtrs)
KLSB - 3	2.5	1.0 ~ 3.0	1.5
			3.0
KI CD E	SB - 5 2.5 2.5 ~ 5.0	25.50	1.5
KF2R - 2		3.0	
KLSB - 7	2.5	4.0 ~ 7.0	1.5
			3.0

KSB Series

Model No	Capacity (Kgs)	Cable Travel (Mtrs)	Diameter of cable (ø mm)	Mass (Kgs)
KSB - 2	0.5 ~ 2.0	1.0	3.0	1.0
KSB - 3	1.0 ~ 3.0	1.3	3.0	1.4
KSB - 5	2.5 ~ 5.0	1.3	3.0	1.5
KSB - 9	4.5 ~ 9.0	1.3	4.0	3.4
KSB - 15	9.0 ~ 15.0	1.3	4.0	3.8
KSB - 22	15.0 ~ 22.0	1.5	5.0	8.0
KSB - 30	22.0 ~ 30.0	1.5	5.0	8.0
KSB - 45	30.0 ~ 45.0	1.5	5.0	11.0
KSB - 60	45.0 ~ 60.0	1.5	5.0	12.0
KSB - 75	60.0 ~ 75.0	1.5	5.0	12.0
KSB - 90	70.0 ~ 90.0	1.5	8.0	23.0
KSB - 110	90.0 ~ 110.0	1.5	8.0	26.0
KSB - 140	110.0 ~ 140.0	1.5	8.0	27.0
KSB - 170	140.0 ~ 170.0	1.5	8.0	28.0
KSB - 200	170.0 ~ 200.0	1.5	8.0	34.0
KSB- 220	200.0 ~ 220.0	1.5	8.0	37.0

KHRB Series

Model	Capacity (Kg)	Hose Travel (Mtr)	Hose ID (mm)	Weight (Kg)
KHRB - 15	0.5 ~ 1.5	1.3	8.5	1.9
KHRB - 25	1.5 ~ 2.5	1.3	8.5	2.0
KHRB - 35	2.5 ~ 3.5	1.3	8.5	2.1
KHRB - 50	3.5 ~ 5.0	1.3	8.5	2.1
KHRB - 65	5.0 ~ 6.5	1.3	8.5	2.2

